



Tunneling Lectures 2011 Speciality Chemicals for Tunnel Boring Machines




Lars Langmaack
Jaime Ibarra




EPB Tunnelling in the Toronto Area

Tunnelling Association of Canada – Ontario Chapter

180 years of TBM History



1825, GB (Thames Tunnel) Sir Marc Brunel




1846, F (Mount Cenis) Henri Joseph Maus



1853, USA (Hoosac Tunnel) Charles Wilson




1869, GB (London) Barlow-Greathead




1882, GB (channel tunnel) Beaumont / English




1907, Germany old Elbtunnel




1931, Germany Schmidt Kranz



1952, USA 1st Robbins TBM




1958, Austria Alpine shield



1965, France (Paris) Robbins, RER System



1968, Germany Wirth TBM



1988 Robbins, Eurotunnel





2006, Spain (Madrid) world's largest EPB





TBM design vs geology



3 main classics



- Foams & Polymers against abrasion and dust
- Main bearing sealant




- Soil conditioning
- Annulus grout
- Tail sealant
- Main bearing sealant



- Tail sealant
- Main bearing sealant



Earth pressure balance (EPB) TBM





Soil Changes with MEYCO SLF soil conditioning agents



dry soil


+ water

+ soil conditioning



Torque Reduction

with MEYCO SLF Foam in Clay Soil, Herrenknecht test rig





Soil types

clay



silt



sand




gravel



boulders




grain size [mm]





soil conditioning and soil mechanics






Example of conditioned EPB soil






actual range of EPB use weak ground under groundwater pressure







importance of EPB driving modes ~~X~~ in soft ground



→ p [bar]



no pressure
open mode




air pressure
 \geq
water pressure



earth pressure
= soil pressure + water pressure



What mother nature gave to us: geological profile





Soil conditioning agents

1. foams


Allow filling of the working chamber
Increase the TBM speed
Reduce abrasion, torque

2. anti-clay-additives

Reduce clogging, adhesion, transport problems
Increase the TBM speed

3. polymers

Increase soil adhesion, impermeability
Reduce liquid soil consistency
Reduce settlements




soil conditioning I

foam




Foam Types

Ionic Classes




Structures






creation of tunnelfoam






soil conditioning system on TBM schematic view





TBM Foam & Polymer parameters





Important: Foam Quality

over wide range of FER and output quantity

FER=8



FER=10



FER=20





EPB Tunnelling in the Toronto Area

Tunnelling Association of Canada – Ontario Chapter

Injection Points at the TBM cutterhead





soil conditioning II anti-clay-additives



change of clay behaviour with Rheosoil anti-clay-additives



Clay + water & foam



Clay +
foam & Rheosoil





Madrid MetroLam project – belt view



foam



foam + RHEOSOIL



soil conditioning III long chain polymers



how do polymers work ?



MEYCO Fix SLF P2



Singapore Metro



only foam used
water content too high



foam with 5% SLF P1
too much polymer used
block creation



foam with 3.5% SLF P1
acceptable situation
2-3% polymer would be sufficient



TBM site examples



EPB Tunnelling in the Toronto Area

Tunnelling Association of Canada – Ontario Chapter

LOVAT EPM TBM





Assembly in the shaft




Lars Langmaack, Jamie Ibarra, September 2011, BASF Construction Chemicals



EPB Tunnelling in the Toronto Area

Tunnelling Association of Canada – Ontario Chapter

Aviles geology





effect of structurizing polymers



2,5 bar sea water pressure
use of foam



2,5 bar sea water pressure
use of foam & polymer



TBM parameters & advance rates

	LUTITES	SAND	SILTY CLAY	DOLOMITE	TOTAL TUNNEL
Average advance (m/day)	16,50	27,00	14,00	20,50	20,00
Max. Advance (m/day)	31,00	50,50	29,00	32,40	50,50
Average excav. time (min/ring)	46,00	16,00	35,00	40,00	24,00
Average installing time (min/ring)	21,00	18,00	15,00	15,00	16,00
Average thrust pressure (Ton)	200-300	600-800	300-500	800-900	
Average torque (Ton x m)	60	80	130	170	




Aviles Collector, Spain successful breakthrough



Lars Langmaack, Jamie Ibarra, September 2011, BASF Construction Chemicals



universal TBMs adoption to geology by soil conditioning




LYON 1997
NFM EPB, $\varnothing=10.98\text{m}$
1.5-3 bar water pressure
foam + polymer + **bentonite**

BARCELONA 2003
Herrenknecht EPB, $\varnothing=12.06\text{m}$
up to 2.0 bar water pressure
foam + polymer + **filler suspension**



Barcelona Metro L9, geological overview





Barcelona Metro L9, project UTE L9



TBM-characteristics:

$d = 11,95 \text{ m}$

$\text{force} = 110 \text{ MNm}$

$\text{torque} = 37 \text{ MNm}$

$\text{power} = 7,15 \text{ MW}$

26% open shield



Barcelona Metro L9, project UTE GORG



TBM-characteristics

$d = 12,06 \text{ m}$

$\text{force} = 110 \text{ MNm}$

$\text{torque} = 38 \text{ MNm}$

$\text{power} = 5,32 \text{ MW}$

35% open shield



Barcelona Metro L9 laboratory tests for porous soil




pure soil

soil with
foam



soil with
more foam

soil with
foam +
polymer +
filler





Toulouse Metro Project



Line B consists of 20 stations,
13.000m bored tunnel

- Lot 2: Herrenknecht EPB TBM
4.731m
- Lot 3: CSM Bessac compressed air TBM
1.000m
- Lot 4: FCB Slurry TBM
3.700m
- Lot 5: FCB EPB TBM
3.400m

Lot 2:
Campenon Bernard TP & Eiffage TP



The TBM



EPB TBM S-208


- shield length: 8,50m
- shield diameter: 7,750m
- cutterhead diameter: 7,785m
- TBM speed \leq 80 mm/minute
- EPB pressure \leq 3 bar.
- installed power: 2.000 kW,
- driving force: 55,75 kN
- jack force: 6.000 tons.

Segments

- diameter: 6,80m (5+1)
- length: 1,40m
- thickness: 340mm.
- total segment number: 26.000
- total muck excavation: 225.000m³
or 517.000 tons



Toulouse Metro project sieve curves



Toulouse (F) '2003


HK EPB, Ø=7.72m

mainly under water table

Foam + Anti-Clay



Toulouse soil parameters (clogging risk after Thewes)





Lab tests with Toulouse soil



Addition of water and standard foam



Addition of water, Foam and RHEOSOIL anti-clay-agent



Toulouse Metro project conditioned soil comparison



dry excavation



homogeneous & plastic soil
with Foam and RHEOSOIL



Toulouse Metro Lot 2 cutterhead comparison



dry mode & empty chamber



plastic mode & full chamber
with RHEOSOIL®



EPB conditioned soil





Worlds biggest EPB TBM Madrid M30 motorway project



With a diameter of 15.20m, the TBMs excavate an area of 181.5m² for implementing a 3 lane motorway including sidewalks.



EPB Tunnelling in the Toronto Area

Tunnelling Association of Canada – Ontario Chapter

Start Shaft North



Lars Langmaack, Jamie Ibarra, September 2011, BASF Construction Chemicals



Worlds biggest EPB TBM, MHI Madrid M30 motorway project, Spain



Lars Langmaack, Jamie Ibarra, September 2011, BASF Construction Chemicals



Worlds biggest EPB TBM, HK Madrid M30 motorway project, Spain





**Anti-Abrasion and Anti-Dust Technology
ABR 5**



typical situations in hard rock TBM excavation

excessive wear is a direct cost issue

- cutter cost
- maintenance cost (cutter changes stressful and time consuming)
- damaged cutters can lead to cutter head damages

down time

- the more frequent cutters have to be changed, the more down time it means for the TBM
- during down time the tunnel does not make any progress!

dust & temperature

- not good for the worker's health
- reduce life-time of equipment
- expensive exhausting



Is really necessary to develop anti-wear products?





why using ABR5?

current practice: injecting water

- *lots of dust is not cached by the water*
- *the cutter temperature can still be higher than 100° C*
- *the use of water contributes to higher cutter wear.*

use of MEYCO® ABR5 makes the difference

- effective dust suppression makes the working environment healthier and increases the life time of the electronic equipment
- cutter temperature can be reduced down to 60-80° C (depending on the conditions) due to better heat transfer and mucking out
- increase of life time of the cutter sealing
- decrease of wear due to lubrication effect and reduced water injection
- decrease of TBM downtime due to reduced maintenance needs




needs to use MEYCO® ABR5

MEYCO® ABR5 is delivered to the cutterhead as a foam.


Therefore foam needs to be generated and transported to a number of different injection points on the cutterhead.

Example Wirth TBM, Guadarrama

installation of a simple rotary coupling
in order to serve independently 5
injection ports on the cutterhead



rotary coupling





needs to use ABR5

For the application, **a dosage pump** is needed to produce an aqueous solution of MEYCO ABR5 which then will be foamed up with **a foam generator**.

dosage pump

- flow up to 10 l/min
- pressure up to 10 bar



foam generator

- 3-5 channels depending on TBM diameter
- typical output per channel: 0.5m³/min





Application Parameters

how much MEYCO® ABR 5 is needed to be effective?

- around 1 litre MEYCO ABR5 per m³ rock in situ

what expansion rate should be used?

- depending on the geological conditions, typical FER of 10-12

how much Foam should be injected?


- typically 250 to 300 litres per m³ rock (FIR=25-30%)

how much additional water should be injected?

- additional water injection can be drastically reduced up to completely stopped (Guadarrama: 50-100 litres instead of > 300 litres)




Guadarrama Project





Guadarrama Rock





Guadarrama High Speed Rail Tunnel

4 hard rock TBM machines

diameter: 9.5m

2 x Herrenknecht

2 x Wirth

2 TBMs drive from the north,
the other two drive from the south

total length: 56 km

geology:

mainly granite, high quartz

content, 100-200 MPa

very high abrasivity



Guadarrama South



situation with only using water




number of cutters changed typically varied from 5-28 per day

high maintenance cost, lot of down time



due to the high temperature, cutters can get blocked (failure of bearing seal)



high temperature and high dust level time consuming disc cutter change




scientific research background





Ball Mill Test Results, Trondheim University, N TBM chips (crushed), Loetschberg, CH





... use of ABR foam on the TBM ...



Lars Langmaack, Jamie Ibarra, September 2011, BASF Construction Chemicals



ABR 5 Benefits

without ABR5



disappearance of dust
longer life time of electronics,
healthier working conditions





clean & cool cutters
easy & quick to change
no muck clogging



drastic reduction of cutter
temperature (150→70° C)
no cutter blockage any more
around 15% wear reduction
reduced downtime

with ABR5





Environmental Studies




Emission possibilities



ground water



landfill



working
environment




General background what do LC₅₀/EC₅₀ data mean?




algues



daphnia magna



rainbow trout



additives [mg/l water]




Landfill of excavated soil





General Risk Characteristics important factors of eco-compatibility

(mammal) toxicity





Environmental Risk Assessments !

MBT International Underground Construction Group

Environmental Risk Assessment

Use of Meyco® Fix SLF in tunnel constructions

May 2001



BMG Engineering Ltd

Swiss Office:
Hansgutstrasse 11
CH-8401 Winterthur
Phone: +41 1 752 95 82
Fax: +41 1 752 95 82
e-mail: bmgbw@bmgbw.ch

Swiss Office:
Grenzach-Wyhlen 18
D-7770 Grenzach-Wyhlen
Phone: +41 61 827 95 90
Fax: +41 61 827 95 90
[www.bmgbw.ch](http://bmgbw.ch)

OSB International, Ltd. (UK):
Hansgutstrasse 11
CH-8401 Winterthur
Phone: +41 1 752 95 82
Fax: +41 1 752 95 82
[www.bmgbw.ch](http://bmgbw.ch)

MBT International Underground Construction Group

Environmental Risk Assessment

Use of Rheosoil® in tunnel constructions

October 2003



BMG Engineering Ltd

Swiss Office:
Hansgutstrasse 18
CH-8401 Winterthur
Phone: +41 61 827 95 80
Fax: +41 1 752 95 80
[www.bmgbw.ch](http://bmgbw.ch)

Swiss Office:
Grenzach-Wyhlen 18
CH-7770 Grenzach-Wyhlen
Phone: +41 61 827 95 80
Fax: +41 1 752 95 80
[www.bmgbw.ch](http://bmgbw.ch)

UK Office:
Hansgutstrasse 11
CH-8401 Winterthur
Phone: +41 61 827 95 80
Fax: +41 1 752 95 80
[www.bmgbw.ch](http://bmgbw.ch)

MBT International Underground Construction Group

Environmental Risk Assessment

Use of MEYCO® Fix TSG in tunnel constructions

December 2002



BMG International/BMG AG

Swiss Office:
Hansgutstrasse 18
CH-8401 Winterthur
Phone: +41 61 827 95 80
Fax: +41 1 752 95 80
[www.bmgbw.ch](http://bmgbw.ch)

UK Office:
Hansgutstrasse 11
CH-8401 Winterthur
Phone: +41 61 827 95 80
Fax: +41 1 752 95 80
[www.bmgbw.ch](http://bmgbw.ch)

Foams & Polymers

Rheosoil®

TSG



Thank you for your
attention